

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 May 2004 (27.05.2004)

PCT

(10) International Publication Number
WO 2004/045243 A1

(51) International Patent Classification⁷: **H04R 1/10 //**
H04M 1/05

(21) International Application Number:
PCT/DK2003/000772

(22) International Filing Date:
10 November 2003 (10.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2002 01731 11 November 2002 (11.11.2002) DK

(71) Applicant (for all designated States except US): GN NET-
COM A/S [DK/DK]; Metalbuen 66, DK-2750 Ballerup
(DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PEDERSEN,
Charles, L. [DK/DK]; Grønnevej 124A, DK-2830 Virum
(DK). BECH, Martin [DK/DK]; Ellehammervej 15,
DK-3600 Frederikssund (DK). BØGESKOV-JENSEN,

Tom [DK/DK]; Birkemosevej 22, DK-3550 Slangerup
(DK). LANGHORN, Karsten [DK/DK]; Præstegårds
Allé 37, DK-2700 Brønshøj (DK).


(74) Agent: LARSEN & BIRKEHOLM A/S; Skandinavisk
Patentbureau, Banegårdspaldsen 1, P.O. Box 362, DK-1570
Copenhagen V (DK).

(81) Designated States (national): AE, AG, AL, AM, AT (uti-
lity model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE
(utility model), DE, DK (utility model), DK, DM, DZ, EC,
EE (utility model), EE, EG, ES, FI (utility model), FI, GB,
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL,
PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL,
SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO utility model (BW),
ARIPO patent (BW), ARIPO utility model (GH), ARIPO
patent (GH), ARIPO utility model (GM), ARIPO patent
(GM), ARIPO utility model (KE), ARIPO patent (KE),
ARIPO utility model (LS), ARIPO patent (LS), ARIPO

[Continued on next page]

(54) Title: A HEADSET



(57) Abstract: A headset (1, 10, 30) e.g. for use in
connection with wireless communication by means
of Bluetooth technology in connection with mobile
telephones, PSTN telephones and the like, which
comprises a housing (2, 3, 11, 28) with a transducer
(5, 12, 27) in the form of a speaker, as well as a
microphone (4, 14, 29) and an ear hook (6, 23, 28).
In a first embodiment, the housing may be constructed
as two shells (2, 3) which may be opened and closed
so that all mechanical parts may be concealed on
the housing when the headset (1, 10, 30) is not in
use, thereby ensuring that the various parts are not
damaged when the headset is stored in a pocket. The
shells (2, 3) may be interconnected by means of a
hinge (7, 8) which has an axis disposed in the same
plane as the surface of the shells. Alternatively, the
shells may be arranged such that the axis is disposed
in a perpendicular plane relative to the surface of
the shells. In a second embodiment, the housing
(11, 28) is formed by a closed housing from which
the ear hook (23, 31) and/or the microphone 13, 26)
may be moved in or out. The invention provides a
headset (1, 10, 30) which is extremely easy to use,
and where all mechanical and electrical parts are well
protected when the headset is not used. Furthermore,
all embodiments may be provided with a lock which
may be mechanical and/or electrical, which ensures

that only the right user can use the headset.



utility model (MW), ARIPO patent (MW), ARIPO utility model (MZ), ARIPO patent (MZ), ARIPO utility model (SD), ARIPO patent (SD), ARIPO utility model (SL), ARIPO patent (SL), ARIPO utility model (SZ), ARIPO patent (SZ), ARIPO utility model (TZ), ARIPO patent (TZ), ARIPO utility model (UG), ARIPO patent (UG), ARIPO utility model (ZM), ARIPO patent (ZM), ARIPO utility model (ZW), ARIPO patent (ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

A headset

The invention relates to a headset comprising a transducer, a microphone and an ear hook for suspending the headset from a user's ear.

5

Such a headset is known from WO 01/86923.

10

This known headset is constructed as a compact unit, where a transducer in the form of a speaker is arranged in a housing, which additionally has hinge parts, where an ear hook and a microphone arm, respectively, are secured via hinge links. When the headset is to be used, the ear hook and the microphone arm are pivoted out from the housing, and the headset is then ready for use, as it can now be suspended from the left or right ear of a user. The headset is very compact and also configured to provide wire-

15

less communications links, e.g. using Bluetooth technology in connection with mobile telephones, PSTN telephones and the like.

20

As mentioned, it is a very compact headset which has a low weight and is therefore very user-friendly, in particular when used for an extended period of time, as it does not cause trouble or inconvenience to a user's ear. Further, in a state of non-use it may easily be stored in e.g. a pocket. However, storing the headset in a pocket involves a certain risk, as it may be damaged, since ear hook and microphone arm are freely exposed to the housing, whereby these parts may be subjected to inexpedient, mechanical loads.

25

Accordingly, an object of the invention is to provide a headset which has all the mentioned advantages of WO 01/86923, but which is less liable to be mechanically damaged.

30

The object of the invention is achieved by a headset of the type stated in

the introductory portion of claim 1, which is characterized in that the transducer, the microphone and the ear hook are encapsulated in a housing or are integral parts of a housing. In this way, the headset appears as a closed capsule in a state of non-use, in which all movable parts are protected.

When, as stated in claim 2, the housing is formed by two shells which are interconnected by a hinge, it is ensured that the shells are always connected with each other so that the one shell, which is e.g. to serve as a cover part, is not lost.

Expediently, as stated in claim 3, the two shells are connected along their outer edge with the hinge by a shaft which is disposed in the same plane as the surface of the shells. This results in a structure which also imparts mechanical advantages, since the various parts to be arranged between the shells do not necessarily have to be disposed in their respective shells when they are interconnected, but may utilize the space between the shells, so that e.g. some of the internal parts of the headset may be stored in a compartment formed by both shells. Also, the entire headset may be constructed as a very flat structure.

In an alternative embodiment, as stated in claim 4, the hinge has a shaft which is perpendicular to the surface of the shells, as the headset may hereby be brought into a state of use merely by rotating the one shell in the same plane relative to the other shell. For some users, this may facilitate handling of the headset when opening and closing it.

Expediently, as stated in claim 5, the transducer and the ear hook are arranged in the one shell, while the microphone is arranged in the other shell, thereby providing an optimum positioning of the transducer at the ear and the microphone as close to the mouth as possible.

In a second embodiment, as stated in claim 6, the housing is formed by a closed housing, which has two recesses from which the ear hook and the microphone arm, respectively, may be moved into or out of the housing. The number of movable parts is limited additionally hereby, since now just movement of ear hook and microphone arm is to take place.

This second embodiment is additionally easy-to-use, if, as stated in claim 7, at least one release button is arranged on the outer side of the housing for activating the movement of the ear hook and/or the microphone arm into or out of the housing. This release function may moreover be arranged in an advantageous manner if, as stated in claim 8, the release button activates the ear hook and/or the microphone arm by means of a spring load, or, as stated in claim 9, if the microphone arm may be screwed into or out of the housing.

Additional alternative embodiments of the headset of the invention are that the microphone arm is telescopic, as stated in claim 10, or is articulated, as stated in claim 11.

Finally, in all embodiments, the headset may be configured such that the housing is provided with a lock for locking the hook, the microphone arm and the transducer inside the housing, as stated in claim 12, thereby reducing the risk of theft, as theft is not attractive since the headset cannot be used without breaking the lock.

If, additionally, the lock is provided with an electrical code activating the electrical parts of the headset, as stated in claim 13, the use of the headset by other persons than the owner is prevented.

The invention will now be explained more fully with reference to the embodiments shown in the drawing, in which

Fig. 1 shows a headset in a first embodiment of the invention,

Fig. 2 shows the headset of fig. 1 seen in the direction of the arrow I in fig. 1,

5

Fig. 3 shows the headset of fig. 1 and fig. 2 in a folded-together state,

Fig. 4 shows the headset of fig. 3 seen in the direction of the arrow IV in fig. 3,

10

Fig. 5 shows a headset in an open state according to the invention in a second embodiment,

Fig. 6 shows the headset of fig. 5 seen in the direction of the arrow VI in fig. 5,

15

Fig. 7 shows the headset of fig. 5 and fig. 6 in a closed state with inserted microphone arm,

Fig. 8 shows the headset of fig. 9 seen in the direction of the arrow VIII in fig. 9, seen closed from behind,

20

Fig. 9 shows the headset of fig. 6 with inserted microphone arm,

25

Fig. 10 shows the headset in an open state in a third embodiment,

Fig. 11 shows the headset of fig. 10, seen from the side, and

Fig. 12 shows the headset of fig. 10, seen from the side in a closed state.

30

In fig. 1, a headset in a first embodiment of the invention is generally desig-

nated 1. As will appear from this figure and figures 2 – 4, the headset consists of two shells which are designated 2 and 3. The two shells are hinged to each other by hinge parts 7, 8 which are provided on each shell, and which may e.g. be formed such that a shaft 9 connects the hinge parts with each other. As will be seen, the shaft 9 is disposed in the same plane as the surface of the shells, which means that the shells may be closed by rotation about the shaft 9, as is also shown in fig. 4. An ear hook 6 is arranged inside or between the shells 2, 3, and, as indicated in fig. 2, this ear hook may assume two positions, viz. a first position in which it is disposed in a recess in the one shell 2, shown at 6, while it is rotated partly out of the shell 2 in the second position, shown at 6a in fig. 2. Further, each of the shells is constructed such that a transducer in the form of a speaker 5 is additionally arranged in the shell 2, while a microphone 4 is arranged in the shell 3. Finally, figs. 1 and 2 show areas 17, which illustrate that these areas may be designed with another colour than the rest of the headset or be coated with metal, perhaps embossed with a logo.

The headset is used as follows:

When it is to be used, the shells are separated from the position shown in fig. 3 and fig. 4 to the position shown in figs. 1 and 2, and then the ear hook is rotated out from the shell 2 and is suspended from a user's one ear. The other shell, which contains the microphone 4, will be positioned along the user's cheek with the microphone as close to the user's mouth as necessary. The embodiment shown in figs. 1 – 4 thus provides a compact headset where all sensitive parts are well protected in a state of non-use, thereby eliminating damage e.g. during transport in a user's pocket.

Although the embodiment in figs. 1 – 4 shows that the hinge parts are formed such that the shells for opening or closing are to be rotated into or out of their planes, nothing prevents the hinge parts from being formed with

a shaft which is perpendicular to the surface of the shells. In such a situation, opening and closing may be performed by displacing the shells relative to each other so that a rotation takes place in their parallel planes.

- 5 Figures 5 to 9 show a second embodiment of a headset according to the invention. In these figures, a headset according to the invention is generally designated 10 and has a disc-shaped housing 11, which is formed with a recess through which a microphone arm 13 with a microphone 14, which is suspended from a shaft 15 arranged inside the housing, may be rotated
- 10 into or out of the housing 11. The rotation of the microphone arm 13 may be established by a spring force impact from a spring 21 arranged on the shaft. This impact may be applied through a locking mechanism, e.g. in the form of a push-button which when activated will cause the spring 21 to force the microphone arm out of the housing 11 through the recess. When the micro-
- 15 phone arm is to be returned into the housing, it is affected by a force acting opposite the spring, and it is retained in the housing by means of the locking mechanism until the locking mechanism is activated again via the push-button.
- 20 As will be seen, the housing accommodates a speaker 12 which may be protected by a tongue 18, which is provided on the microphone arm, and which will cover and protect the speaker 12 when the microphone arm is moved inwards through the recess.
- 25 An ear hook 23 is arranged on the underside of the housing 11 in a recess whose contours are indicated at 19, and this ear hook may be released from the housing 11 and be suspended from a user's ear by means of a hinge 20.
- 30 Finally, it is indicated at 17 that, for reasons of design, the microphone arm may be given a different colour in this area.

The headset of figures 5 – 9 is unique in that all electrical and mechanical parts are well protected when the headset is not in use.

5 Figs. 10 – 12 show a headset which is generally designated 30. As will be seen, this headset consists of a disc-shaped housing 28 which centrally carries a speaker 27. Two recesses are provided along the edge of the housing, of which the first recess serves to store a flexible microphone arm 26 with a microphone 29, it being possible to bend the microphone arm into the one recess which extends elliptically, as shown. Moreover, the micro-
10 phone arm is formed with a tongue 32 which closes and opens, respectively, the speaker area 27 when the microphone arm is moved from the open to the closed state, and vice versa. In addition, a recess 25 is provided on the opposite side of the housing 28, which is adapted to receive a rotatable ear hook 31. This ear hook 31 may be constructed in the same
15 manner as is explained in connection with the embodiment which is shown in figs. 7 – 9.

The headset of figs. 10 – 12 is used in the following manner:

20 When it is to be used, the microphone arm and the ear hook are released from their positions in the closed headset, so that the speaker is exposed and the ear hook may be arranged on a user's ear, whereby the microphone arm assumes an operating position along the user's cheek.

25 In a variant of the headset shown in figs. 10 – 12, the microphone arm may be constructed such that it is moved into and out of the housing in a channel provided along the outer side of the housing.

30 Finally, it is noted that the microphone arm itself may be telescopic or articulated in structure if further space saving is needed in the housing when the headset is in a state of non-use.

PATENT CLAIMS

1. A headset (1, 10, 30) comprising a transducer (5, 12, 27), a microphone (4, 14, 29) and an ear hook (6, 23, 28) for suspending the headset (1, 10, 30) from a user's ear, c h a r a c t e r i z e d in that the transducer (5, 12, 27), the microphone (4, 14, 29) and the ear hook (6, 23, 31) are encapsulated in a housing or are integral parts of a housing.

2. A headset according to claim 1, c h a r a c t e r i z e d in that the housing is formed by two shells (2, 3) which are interconnected by a hinge (7, 8, 9).

3. A headset according to claim 2, c h a r a c t e r i z e d in that the two shells (2, 3) are connected along their outer edge with the hinge by a shaft (9) which is disposed in the same plane as the surface of the shells.

4. A headset according to claim 2, c h a r a c t e r i z e d in that the hinge (7, 8) has a shaft which is perpendicular to the surface of the shells.

5. A headset according to claims 2 – 4, c h a r a c t e r i z e d in that the transducer (5) and the ear hook (6) are arranged in the one shell (2), while the microphone (4) is arranged in the other shell (3).

6. A headset according to claim 1, wherein the microphone (14, 29) is mounted on a microphone arm (13, 26), c h a r a c t e r i z e d in that the housing is formed by a closed housing (11, 28), which has two recesses from which the ear hook (23, 31) and the microphone arm (13, 26), respectively, may be moved into or out of the housing.

7. A headset according to claim 6, c h a r a c t e r i z e d in that at least one release button (15) is arranged on the outer side of the housing (11) for

activating the movement of the ear hook (23, 31) and/or the microphone (13, 25) into or out of the housing.

5 8. A headset according to claim 7, characterized in that the release button (15) activates the ear hook (23, 31) and/or the microphone arm (13, 26) by means of a spring load (21).





10 9. A headset according to claim 6, characterized in that the microphone arm may be screwed into or out of the housing (11).

10. A headset according to claim 6, characterized in that the microphone arm is telescopic.

15 11. A headset according to claim 6, characterized in that the microphone arm is articulated.

20 12. A headset according to claims 1 – 11, characterized in that the housing (2, 3, 11, 28) is provided with a lock for locking the ear hook (6, 23, 31), the microphone (4, 14, 29) and the transducer (5, 12, 27) inside the housing.

25 13. A headset according to claim 12, characterized in that the lock is provided with an electrical code for activating the electrical parts of the headset.






FIG. 7




FIG. 5




FIG. 6




FIG. 9




FIG. 8




FIG. 10




FIG. 11




FIG. 12

INTERNATIONAL SEARCH REPORT

International Application No

PCT/DK 03/00772

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04R1/10 //H04M1/05

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04R H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2002/021800 A1 (BJERRUM-NIESE CHRISTIAN ET AL) 21 February 2002 (2002-02-21) paragraph [0046] - paragraph [0059]	1-4
Y	---	6
Y	PATENT ABSTRACTS OF JAPAN vol. 2002, no. 05, 3 May 2002 (2002-05-03) & JP 2002 009908 A (SHINWA KOGYO KK), 11 January 2002 (2002-01-11) abstract	6
A	---	1
	US 6 359 995 B1 (OU JACK) 19 March 2002 (2002-03-19) column 1, line 43 -column 2, line 7 -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

23 February 2004

Date of mailing of the international search report

11.03.2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

FREDRIK WAHLIN/MN

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inte.

Application No

PCT/DK 03/00772

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002021800	A1	21-02-2002	DK 200000765 A 10-11-2001
			AU 5211501 A 20-11-2001
			CA 2406609 A1 15-11-2001
			CN 1428038 T 02-07-2003
			WO 0186923 A1 15-11-2001
			EP 1282974 A1 12-02-2003
			JP 2003533135 T 05-11-2003
			NO 20024963 A 18-12-2002

JP 2002009908	A	11-01-2002	NONE

US 6359995	B1	19-03-2002	NONE
